



- NOTES:**
1. TWO CONCRETE BLOCKS SHALL BE PLACED ON THEIR SIDES ABUTTING THE CURB AT EITHER SIDE OF THE INLET OPENING. A 2" x 4" STUD SHALL BE CUT AND PLACED THROUGH THE OUTER HOLES OF THE SPACER BLOCKS TO BRACE THE FRONT BLOCKS. FRONT BLOCKS ARE PLACED ON THEIR SIDES ACROSS THE INLET AND ABUTTING THE SPACER BLOCKS.
  2. WIRE MESH OR HARDWARE CLOTH WITH 1/2" - 1/2" OPENINGS SHALL BE PLACED OVER THE OUTSIDE VERTICAL FACE (WEBBING) OF THE BLOCKS, TO PREVENT STONE FROM BEING WASHED THROUGH THE HOLES IN THE BLOCKS.
  3. STONE SHALL BE PILED AGAINST THE WIRE TO TOP OF BLOCK. (NCDOT #57 WASHED STONE)
  4. CHECK DEVICE AFTER EACH RAIN AND REPLACE WASHED STONE IF IT CLOGS WITH SEDIMENT.

CITY OF HIGH POINT  
 NORTH CAROLINA  
 ENGINEERING SERVICES DEPARTMENT  
 APPROVED... FEBRUARY 17, 2009  
 BSK  
 DIRECTOR

ISSUED 2-17-09  
 REVISIONS

STANDARD DRAWING FOR  
**BLOCK AND GRAVEL CURB INLET PROTECTION**  
 FOR TYPE A AND TYPE B CATCH BASINS

INLPRO CURB.DWG

608.02

SHEET 1 OF 1